

### FEATURES

- Multi-format scan conversion
- Input/Output resolutions up to 2K x 2K
- Full range of analog and digital inputs and outputs
- Mix and synchronize different video standards
- Optional: Video-over-IP; H.264 Video Compression w/ MPEG-2 compliant TS multiplexing
- Fully configurable network interface
- Front Panel, or command line control (RS-232 or Ethernet )
- 1RU Package
- +10°C to +71°C Operation



The Model VSC/900 provides scan conversion and mixing for any video input signals. The unit's capabilities include conversion of any input to any output format up to 2K x 2K. In addition to operating with VESA, HD and SD signals, the unit provides conversion and mixing of stroke (vector) video signals.

The VSC/900 has an integrated mixer/keyer for combining computer graphics and video. An optional video encoder can be included to provide video-over-IP functionality. This is an H.264 AVC encoder providing an MPEG-2 compliant transport stream over a fully configurable IP network.

The unit is a 1RU package with a front panel control interface. The rear panel provides a full range of analog and digital inputs and outputs including HD-SDI, DVI, composite and vector signals.

## UNIVERSAL VIDEO FORMAT CONVERTER

### Vector Signal Inputs

#### X & Y Analog Deflection Inputs (2)

Balanced or Unbalanced, 1 to 30 V p-p, loop-through, Impedance > 7K ohm

Offset range: +/- 50% of input

Signal Inversion

#### Z Analog Intensity Inputs (4) (red, green, blue, and monochrome)

Balanced or Unbalanced, 0.5 to 20 V p-p, loop-through, Impedance > 7K ohm

Signal Inversion

#### Z Digital Intensity Inputs (1) (monochrome)

TTL or Differential TTL (RS-422)

Signal Inversion

#### Stroke/Raster Input

TTL or Differential TTL (RS-422)

### Video Signal Inputs and Outputs

Analog, Composite with color burst (CVBS) – BNC Connector (1 in, 1 out)

Analog, RGB or monochrome (Sync on green or separate H & V), or Analog, YPrPb – VGA Connector (1 In, 2x out)

Digital DVI, Single-Link – DVI Connector (1 in, 2x out)

Digital SDI – BNC Connector (1 In, 1 out)

**Size:** 19"x12"x1.75"

**Weight:** 6.2 Lbs.

**Power:** 110 to 240 VAC, 50-400 Hz. 75 W

### Video Standards Supported

NTSC PAL

VGA (640x480)

SXGA (1280x1024)

WUXGA (1920x1200)

HDTV 1080P

STANAG(ABC)

SVGA (800x600)

SXGA+ (1400x1050)

HDTV 720P

RS-343(675,729,875 lines)

XGA (1024x768)

UXGA (1600x1200)

HDTV 1080I

